

## **OZEKI NG – SMS GATEWAY**

PRODUCT DATASHEET Last updated: 7. Jan 2008.

OZEKI NG – SMS Gateway	
OZEKI NG	OZEKI NG – SMS Gateway is a high capacity SMS server that is very popular among ISV/OEM, Enterprise, and Community Users. It is recognized for its superior ease of use, performance and reliability.  The software can be used to send and receive SMS text messages and various other message types, such as WAP push messages, operator logos and ring tones. The sending is done through IP SMS connections or GSM Modem connections.  OZEKI NG – SMS Gateway makes it possible to connect any application implementing business logic directly to the Short Message Service Center (SMSC) of a GSM service provider. This connection is possible through the Internet or through a leased line. Software developers and system integrators prefer OZEKI NG – SMS Gateway, because it provides easy to use connectivity options and application programming interfaces (APIs) for both sending and receiving.  Concerning performance, the software has an outstanding capacity. It can serve 300 sms/second on several SMSC connections simultaneously on a standard Intel P4D, 3GHz 1GB RAM computer. The server can handle large number of concurrent applications and user connections.
	7 days a week under heavy duty. It manages network link failures, network service provider failures, tolerates hardware reboots.
Website	http://www.ozekisms.com
E-mail	Sales information: info@ozekisms.com
Dackago	Technical information: techsupport@ozekisms.com
Package contents	CD ROM – Software Installation Package CD ROM – Full product documentation
	License certificate
	Printed product documentation (optional)
License	Commercial, lifetime
Technical support	Live technical support is available over telephone / e-mail / Instant messaging in business hours (Mon-Fri, 9 a.m. to 5 p.m. GMT+1). On site support is also possible provided the travel expenses are covered. Please note that once the software is installed and configured properly usually very little support is requied



OZEKI NG – SMS Gateway		
OS Support	Windows 2000 Windows 2000 Server (Standard Edition, Enterprise, Datacenter) Windows XP (Home Edition, Professional) Windows 2003 Server (Standard Edition, Enterprise, Datacenter, Web Edition) Windows Vista	
Hardware	CPU: Pentium IV 3 GHZ or Compatible, RAM: 1 GB HDD: 40 MB free disk space	
Network connection Features	ISDN, ADSL, Cable, T1, Lease line, Ethernet or any other internet connection  Message queues (store and forward) Message routing Multi user architecture Multiple SMSC connections Network link management Load balancing API-s for programming languages	
Clients	Outlook client Excel client Ozeki client	
Capacity	Depends on the hardware. With an Intel P4D 3Ghz CPU, 1 GB RAM, you can expect the following capacity:  300 messages / second	
Supported protocols	SMPP 3.3 / 3.4 UCP/EMI 4.0 CIMD 2.0 GSM Modem HTTP Client / Server	
Limitations	The limitations depend on the license you purchase. Licensing information is available at: <a href="http://www.ozekisms.com/index.php?owpn=242">http://www.ozekisms.com/index.php?owpn=242</a> The license type determines the following:  - The message capacity - How many service provider connections can you setup - How many applications (or users) can be configured on the system	
API-s	SQL, HTTP, ASP 2.0 / ASP, Visual Basic, C#, C/C++, Delphi, Java, JSP, Coldfusion, PERL, PHP, Ajax, Atlas, Lotus	
Message types	GSM Text SMS, Unicode Text SMS, Multipart (Concatenated) SMS messages, Flash SMS, Group graphics, Operator logos, Ring tones, WAP push messages, Screensavers, Nokia business card (VCard), Nokia calendar (VCalendar), Bookmarks, Animations, EMS, Binary messages,	